

Amendments to the Specification:

Please replace the paragraph beginning on page 2, line 24, with the following amended paragraph:

--In one form, although it need not be the only or indeed the broadest form, the invention resides in a method of ordering a translation of an electronic communication including the steps of:

displaying simultaneously to a user;

at least part of said electronic communication; and

a one-click translation component, said translation component comprising an object identified as effecting a translation of said electronic communication;

said user clicking said one-click translation component to request translation of a selected said electronic communication;

said one-click translation component requesting a translation of said selected electronic communication by transmitting said selected electronic communication, or an indicator of said selected electronic communication, to a translation manager;

said translation manager obtaining a translation of said electronic communication; and

said translation manager directing transmission of said translation of said electronic communication to said user.--

Please replace the paragraph beginning on page 3, line 7 with the following amended paragraph:

--In a further form, the invention resides in a single-click translation ordering system comprising:

a one-click translation component displayed simultaneously in association with at least part of an electronic communication, said translation component comprising an object identified as effecting a translation of said electronic communication;

Appl. No. 09/676,690
Amdt. dated August 5, 2004
Reply to Office Action of May 10, 2004

a translation manager in communication with said one-click translation component via a communication network, said translation manager obtaining a translation of a selected said electronic communication in response to a single action by a user to clicking said one-click translation component, and directing transmission of said translation of said selected electronic communication to the user.--